

Registered Office & Plants

"Murudeshwar Bhavan", Gokul road, Hubli - 580 030.

UNIT - 1

Krishnapur village, Old Hubli, Hubli - 580 024.

UNIT - 2

143, Illayanacudy Road, Devampuram village Thirunallur Panchayat, karaikal - 609 607.

UNIT - 3

Survey No. 139 And 141/1 Huildore village, Bukkapatna Hobli, Taluk:Sira Dist:Tumkur.

www.naveentile.com



Tiles
For Exquisite
Lifestile!

20 25 COLLECTION

GVT & PGVT

COLLECTION

600X600MM | 600X1200MM











Murudeshwar Ceramics Ltd.

Since its inception in the year 1983, Murudeshwar Ceramics Ltd. (MCL) has steadily progressed to become one of India's largest tiles manufacturing company, producing the widest range of products in Ceramic Floor tiles, Digital Wall tiles, Vitrified full body, Nano Soluble Salt tiles, Gvt - Pgvt tiles, Parking tiles, Double charge tiles and have become synonymous with quality.


The company through the years, has earned many distinctions, like being the first to produce and export large format Vitrified tiles in India, the largest manufacturer of vitrified tiles, and so on, It has three large-scale, state-of-theart manufacturing facilities (at Hubli Karnataka, Bukkapatana-Bangalore Karnataka and Karaikal, Pondicherry).

Which is in technical collaboration with the World-leaders Sacmi Imola and Breton, Italy, with an unfailing commitment to excellence, it utilizes the finest of raw materials and rigorously cheeks and controls the quality of the tiles.

Over the years, the company has established a great reputation for its manufacturing capabilities, which is backed by the R&D cells attached to the manufacturing facilities. this ensures the company stays abreast of the latest global trends constantly developing innovations in colors, designs, textures, finishes, and sizes.


Naveen Diamontile products are certified in accordance with Indian & European Standards, the most complete and global expression for an industrial company.











7109 ATTICA WHITE


Finish. GLOSSY

600x1200mm

9mm Thickness

TOTAL FACES | 3





7109 ATTICA WHITE











7117 ASTRA BEIGE





7128 CRYSTAL ONYX



7124 BRECCIA AURORA





7162 MARCUS BIANCO



7135 DESSERT GRAVEL



7154 LUCENT ONYX



7177 ROYAL BOTTOCHINO



7151 LUMIX GREY



7135 DESSERT GRAVEL

Wall

7135 Dessert Gravel 600x1200mm 7135 Dessert Gravel 600x1200mm

Floor













7126 BROKIS MOKA LT



7125 BROKIS MOKA DK















SPL 7409 LUCENT BIANCO



4254 MIZAR



3903 ARIC GRIS



4370 LARA CREMA



4393 AMAZON AZUL



5103 SPECTRA WHITE



4394 AMAZON BLACK



5108 SPECTRA LAVA





7180 ROYAL DYNA

4209 VIVAAN






Witness the Glorious Design Pick

MURUDESHWAR CERAMICS LTD.

Craft an incredible space with our glossy surface with spectacular designs.

Sizes. 600x1200mm




5108 SPECTRA LAVA

Wall

5108 Spectra Lava 600x1200mm

Floor

5108 Spectra Lava 600x1200mm













7149 FLUNO BEIGE

Finish. GLOSSY

600x1200mm 9mm Thickness

TOTAL FACES | 4







7149 FLUNO BEIGE









7138 DAMASCO GREY











7160 MARSA DUNE DK









7166 MARMI GREY DK 7176 PERLINO GRIS















5334 TEAKWOOD BROWN




3615 KING WOOD BROWN





www.naveentile.com











4227 TREVISO

Finish.

GLOSSY

600x600mm

9mm Thickness



21

4209 **VIVAAN**

Finish.

GLOSSY

600x600mm

9mm Thickness



4209 VIVAAN







24





4245 VEGA

4272 KRISBA



4388 ALMOND WHITE

4373 CALIFORNIA ICE

4370 LARA CREMA






4254 MIZAR

5103 SPECTRA WHITE








4391 CANTO GREY

7109 ATTICA WHITE







1055 AGRIYA WHITE

4387 ALMOND GREY

4395 AMAZON BLUE




4387 ALMOND GREY















4393 AMAZON AZUL



4383 ALMOND BLUE




4394 AMAZON BLACK



4218 RIMINI




4353 IONOCA BLUE



4404 VINTAGE



5108 SPECTRA LAVA





4404 VINTAGE











4119 VOLGA BLUE

4128 VOLGA GREY





4137 VOLGA IVORY

4146 VOLGA BLACK



4137 VOLGA IVORY















4029 PARANA

Finish.

MATT

600x600mm

9mm Thickness



4512 ORANGE SLATE

Finish.

MATT

600x600mm

9mm Thickness




4512 ORANGE SLATE















4623 BOLIVAN WOOD





4047 ENZO

4056 IMOLA

4506 CANARY WOOD

4065 CEDRON 4524 TOPOLI WOOD









4038 HUGO

4191 CINNAMON BIGE

4785 CEMENT DULL





4636 NUGGET WOOD

31





4074 FANTASIA

4628 WANWOOD NATURAL

4065 CEDRON 32











The Wooden Design That Amaze

Let your floors brings natural charm with surfaces that resemble wood.

Sizes. 600x600mm



4636 NUGGET WOOD

Floor

4636 Nugget Wood 600x1200mm



TECHNICAL SPECIFICATION

Sr. No.	Tests	Test Result	Test Method	Requirements IS:15622/2017 Group Bla
(A)	Dimensions and surface quality (Clause-6) (Table No-9)			
01	Length and width			
02	The deviation in percent of the average size of each tile (2 or 4 sides) From the work size (W)	0.017	IS:13630(P-1)-2006	Un-rectified N≤20cm:±0.6 N>20cm:±0.4 Rectified N≤20cm:±0.3 N>20cm:±0.1
03	The deviation in percent of the average size of each tile (2 or 4 sides) from the average size of the 10 test specimen (20 or 40 sides)	+ 0.02500 -0.01666	IS:13630(P-1)-2006	Un-rectified N≤20cm:±0.5 N>20cm:±0.4 Rectified N≤20cm:±0.2 N>20cm:±0.1
04	Thickness The deviation in percent of the average thickness of each tiles from the work size thickness	-0.22	IS:13630(P-1)-2006	N≤20cm:±10 N>20cm:±5
05	Straightness of sides The maximum deviation from straightness. in % related to the corresponding works sizes	+0.035 -0.030	IS:13630(P-1)-2006	Un-rectified N≤20cm:±0.5 N>20cm:±0.3 Rectified N≤20cm:±0.3 N>20cm:±0.1
06	Rectangularity The maximum deviation from rectangularity in % related to the corresponding work sizes	+0.032 -0.023	IS:13630(P-1)-2006	Un-rectified N≤20cm:±0.6 N>20cm:±0.3 Rectified N≤20cm:±0.3 N>20cm:±0.1
07	Surface quality	>95	IS:13630(P-1)-2006	Minimum 95% of tiles shall be free from visible defects that would impair the appearance of a major area of tiles
08	Surface Flatness The maximum deviation from flatness in %		IS:13630(P-1)-2006	
09	Center curvature, related to diagonal calculated from the work size	+0.022 -0.018		N≤20cm:±0.75 N>20cm;±0.5
10	Edge curvature, related to the corresponding works sizes	+0.035 -0.030		N≤20cm:±0.75 N>20cm;±0.5
11	War page, related to diagonal calculated from the work size	+0.020 -0.016		N≤20cm:±0.75 N>20cm;±0.5
(B)	Physical Properties (Clause-6)(Table No-9)			
01	Water Absorption, (% by wt) Average	0.033, 0.025, 0.024 0.024, 0.033, 0.028	IS:13630(P-2)-2006	Individual 0.1, Max Average≤ 0.08
02	Modulus of ruptures, (N/mm) Average	36.1, 37.4, 36.7, 35.6 36.9 36.5	IS:13630(P-2)-2006	Individual 32, Min Average 35
03	Scratch hardness of surface, (Mhos)	6	IS:13630(P-13)-2006	5, Min
04	Thermal shock resistance	Passes the test	IS:13630(P-5)-2006	10 Cycles, Min
05	Breaking Strength (N)	2441	IS:13630(P-6)-2006	700, minimum for thickness < 7.5mm 1300, minimum for thickness > 7.5mm
06	Co-efficient of linear thermal expansion from ambient temperature to100°C (K ⁻¹)	0.0×10 ⁻⁶	IS:13630(P-4)-2006	6x10 ⁻⁶ max
07	Moisture expansion, in mm/m	0.0	IS:13630(P-3)-2006	0.02, Max
08	Impact resistance coefficient of restitution	0.93	IS:13630(P-14)-2006	0.55, Min
09	Resistance to deep abrasion of unglazed tiles, volume of material removed in cubic millimeter (Applicable for floor application only)	74	IS:13630(P-12)-2006	140, Max
10	Bulk density, in g/cc	2.28	IS:13630(P-2)-2006	2.2 Min
11	Frost resistance	Not show any damage on proper surface and edges of the tiles after 50 cycles.Passes the test	IS: 13630 (P-10)-2006	
(B)	Chemical properties (Clause-6)(Table No-9)			
01	Resistance to staining	Passes the test class-2	IS: 13630 (P-8)-2006	Glazed tiles class 1,min Unglazed tiles class 2, min
				Crigiazoa tilos ciaso Z, IIIII

PACKING DETAILS

Sr. No	Size(mm)	No of tiles per box	Weight / Box	Coverage area per box
1.	600x1200 mm	2 Pcs.	28.5 Kg.	1.44 sq. mtr.
2.	600x600 mm	4 Pcs.	30.5 Kg.	1.44 sq. mtr.

Vitrified tiles have resistance to most of the stains / chemicals but it is recommended to take due care while laying and for day today maintenance

The reproduction of tiles in this catalogue is restricted to four colour printing only and tiles are not relative sizes. Conforming to ISO requirements, technical specifications for Naveen tiles are applicable only for 1' quality tiles. please inspect all tiles prior to installation; company will not entertain complaints, once tiles are laid / fixed. Price category & PEI grade may change without any notice. Customers are advised to confirm it before placing order.



www.naveentile.com